

The **Logopak** 920 range for pallets and large products.



This is a larger footprint Thermal-Transfer / Thermal-Direct print & apply labeller with a print speed of up to max. 150 mm/sec and an **iLEAP64** controller that works with flat head print plates.

Logopak has developed and designed the print head with internal electronic control, which permanently checks all of the print head dots and adjusts as required.

The unit is supplied in a number of parts custom designed for the application in question by **Logopak** engineers.

Constructed from **Logopak** designed components with little or no plastic items used in its manufacture to ensure longevity of life.

The **Logopak** 920 is mainly used for the application of

labels to Pallets. However due to the facility to print & apply labels which are slightly larger than A4, the **Logopak** 920 has uses in many industries.

Installed in quantity in high speed pallet lines and in producers of bulk product, the 920 range is the most

industrial label applicator available in the market today.

Integrated scanning, steel enclosures, pressurised and sometimes heated, operating trapdoors, raising & lowering & double head applicators are all options designed to maximise the efficiency and life of these units.



SPECIFICATION

Interface: Standard 4 x V24 / RS232 serial up to 115KBPS with an industrial field bus for I/O control

Optional: 20mAmp, RS 422, RS485, Ethernet and bolt on RF

Baud rate: Variable up to 115.600 baud

Temperature: From 15°C to 45°C.

Humidity: From 15 to 85%

Fonts: 10 as Standard, 4 Scaleable, extras as option.

Graphics mode: 100%

Barcodes: All general plus 2D.

Print speed: Variable from 80 mm to 150mm/sec.

Labelling speed: Up to 90 ppm dependant on label size and applicator variant.

Paper width: 225 mm with backing.

Print Width: 216mm 8 or 12 dot/mm

Print length: Up to 450mm

Label reel O/D: 400mm 780M paper length with standard papers.

Carbon Transfer ribbon: 800M length.

Processor: Dual 64 bit RISC processor, 150MHz clock frequency.

Memory: 1 MB CMOS-Ram expandable to 8 MB

Work & Graphic memory: Each 16 MB expandable to 64 MB.

Display: Colour VGA LC-Display with touch-screen, Multi-lingual operator interface.

Remote Service module (analogue): standard.

Optional: VGA Monitor, Integrated bar code scanning, machine enclosures, alarm poles, **8 applicator units as standard**, centralised data control software.

RFID: Fitted from source or retro-fitted later.

Logopak have been at the leading edge of the development of print & apply solutions for the market place since the mid 1980s and we are still resolute in our core philosophy of robust engineering, which is built to suit modern high speed, low manned production plants.

At **Logopak**, we have always tried to ensure that the build quality of our products far exceeds the criteria which today's end user demands of his purchases.

Other Product Ranges.

806 / 901

Lower speed print & apply labelling solutions.

906

Medium to high speed print & apply solutions

920

Wide web medium to high speed print & apply solutions

920P/PF/PFR - K - DK

Medium to high - speed Pallet labelling solutions

2906

Very high speed print & apply labelling solutions

2920 /PF/PFR - K - DK

Medium to high - speed Pallet labelling solutions.

VLP 110 & 210

Off-line industrial printer solutions.

RTP

Tote & Returnable Transit Package labelling solutions.

Distributed by
TSC Barcode Solutions Ltd
20 Salisbury Rd Business Park,
Pewsey,
Wiltshire, SN9 5PZ
Tel 01627 563124
fax 01672 555461
info@tscgroup.co.uk
www.tscgroup.eu